

Model

IES-BATT-186R



[Overview]

Indoor battery rack with IP20 protection level,
inbuild lithium-ion battery and BMS

[Easy Installation and Maintenance]

Local and remote management, standard
rack&module design, front maintenance

[Safe & Reliable]

Self-developed 2-level / 3-level BMS,
multiple protection, safe and reliable

[High Density]

High capacity LFP battery

[Long Lifespan]

Long cycle life, 8000 cycles *

[Cell Balancing Technology]

Advanced cell balancing

DATASHEET

Model	IES-BATT-186R
-------	---------------

Performance

Battery module (Wh/V)	14.336 kWh, 51.2 V, 110 kg (242.5 lbs)
Number of modules	13
Cell technology	LFP (LiFePO4)
Battery usable energy [1]	186.368 kWh
Nominal voltage	665.6 V
Operating voltage	582.4 - 730.08 V
Nominal output current	140 A / 280 A

Communication

Display	SOC status indicator, LED indicator, LCD display
Communication	Ethernet / CAN / RS485

General Specification

Dimension (W*D*H)	1721x840x1776 mm 67.8x33.1x69.9 inch
Weight	1760 kg (3880 lbs)
Operating temperature [2]	-20 to 60 °C (-4 to 140 °F)
Environmental humidity	≤ 95%RH (No condensation)
Protection rating	IP 20
Cycle life [3]	8000 Cycles or ten (10) years @ 80% DOD / 25°C / 0.5C, 70% EOL
Scalability	Yes
Application	ON Grid / ON Grid + Backup / OFF grid
Compatible PCS	Refer to compatible PCS list

Standard Compliance

Cell: UN38.3 / IEC62619 / UL 1642 / JET
Pack: UN38.3 / IEC62619 / IEC61000

Ordering and Deliverable Part

Part	IES-BATT-14.3P-F-QC
	IES-BCU-M-186H1-QC
	IES-R18

[1] Test conditions: 100% depth of discharge (DOD), 0.2C rate charge & discharge at 25°C.

[2] Charge/discharge derating occurs when the operating temperature from -10°C to 5°C & 45°C to 55°C.

[3] Please refer to the Warranty Letter for applicable conditions, the warranty is due whichever comes first.